

RK-440

4U Rackmount Industrial Chassis supports 19-slot Backplane & Redundant Power Supply



Specifications

Dimensions	19 in x 7 in x 26.4 in (480 mm x 177 mm x 671 mm) (W x H x D)
Drive Bays	Three 5.25" and one 3.5" front accessible drive bays
Construction	Heavy-duty steel
Color	Black
Cooling Fans	Four 9-cm ball bearing fans, 51 CFM each
Front Panel	Front door with lock LEDs: HDD active, system power System reset switch, ATX power switch
Backplane	Support 19-slot passive backplane
Carton Size	33.5 in x 24.4 in x 13.6 in (850 mm x 620 mm x 345 mm)
Weight	Net 24.5 kg (53.9 lb)

Backplane Options

Model Name	PICMG® SBC	PCIe x1	PCIe x4	PCIe x16	PCI	ISA	PSU Connector
HPCI-19S18A	2	--	--	--	18	1	ATX/AT

Mechanical Layout



Features

- EIA RS-310C 19" rackmount standard
- Supports 19-slot backplane and mini redundant power supply
- Three 5.25" and one 3.5" shock-resistant drive bays
- Adjustable hold down bar for cards

Power Supply Options

Model Number	Watt	Input Range	Output (Max.)					
			+5 V	+3.3 V	+12 V	-12 V	-5 V	+5 Vsb
APS-940XAR-EPS12 (for RK-440) (Mini Redundant)	400 W	Universal	35 A	25 A	28 A	1.2 A	0.5 A	2 A
APS-946XA-EPS12 (for RK-440)	460 W	Universal	40 A	30 A	32 A	1 A	0.8 A	2 A

Ordering Information

Model Number	Color	Description
RK-440	Black	4U rackmount industrial chassis supports 19-slot backplane

Dimensions

Units: mm

