

# RK-608MB

## Wallmount Chassis for ATX Industrial Motherboard



### Features

- Supports Mini-ITX, microATX, FlexATX, ATX industrial motherboards
- One 5.25", two 3.5" external drive bays and three internal 3.5" drive bays
- Drive bay with shock and vibration resistant design
- Two USB and one PS/2 keyboard connectors on front panel
- 12cm cooling fan (85 CFM)
- PS2 ATX power supply

### Specifications

Dimensions	13 in x 7.7 in x 16 in (330 mm x 196 mm x 406 mm) (W x H x D)
Drive Bays	One 5.25", two 3.5" external drive bays and three internal 3.5" drive bays
Construction	Heavy-duty steel
Color	Standard: Beige
Cooling Fans	In: one 120mm x 120mm x 25mm ball bearing fan (85 CFM)
Front Panel	LEDs: HDD active and system power System reset switch and ATX power switch Two USB and one PS/2 keyboard connectors
Backplane	Mini-ITX, microATX, FlexATX, or ATX industrial motherboard
Power Supply	PS2 form factor ATX power supply
Carton Size	20.9 in x 13.2 in x 18.1 in (530 mm x 335 mm x 460 mm)
Weight	Net 7.8 kg (17.2 lbs)

### Ordering Information

Model Number	Color	Configurations / Power Supply
NS-608MB-350	Beige	APS-935XA-EPS12
NS-608MB-M302-64-00	Beige	M302, RK-608MB, Intel® Core™2 Duo E6400 2.13GHz, 2G RAM, 400W PSU
NS-608MB-M302-64-01	Beige	M302, RK-608MB, Intel® Core™2 Duo E6400 2.13GHz, 2G RAM, 400W PSU, Windows® XPP Embedded
NS-608MB-M302-44-00	Beige	M302, RK-608MB, Intel® Celeron® 440 2.0GHz, 1G RAM, 350W PSU
NS-608MB-M302-44-01	Beige	M302, RK-608MB, Intel® Celeron® 440 2.0GHz, 1G RAM, 350W PSU, Windows® XPP Embedded

The above listed models are equipped with HDD, DVD±R/RW  
Contact your ADLINK representative for different CPU, memory combinations.

### Mechanical Layout



### Dimensions

Units: mm

